



**DATA CHART**

ITEM NO.		GALLON CAPACITY	A	B	C	D	E	APPROX. WEIGHT
STD.	HD.							
RST 1000-LB	RST 1000-LB -HD	1,000	10'-6"	6'-4"	4'-0"	3'-1"	2'-6"	8,100 LBS.
RST 1250-LB	RST 1250 -LB-HD	1,250	10'-6"	6'-4"	4'-7"	3'-8"	3'-1"	10,500 LBS.
RST 1500-LB	RST 1500 -LB-HD	1,500	10'-6"	6'-4"	5'-0"	4'-2"	3'-7"	11,000 LBS.

\*NOTE: FOR HEAVY-DUTY TANKS (HD), ADD 6" TO DIMENSIONS IN COLUMN C AND 3" TO THOSE IN COLUMN D.

**DESIGN DATA & GENERAL NOTES**

- 1) CONCRETE: 4,000 PSI @ 28 DAYS.
- 2) CEMENT: PORTLAND TYPE III PER ASTM C150
- 3) REINFORCING: 6X6X10WWM OR FIBERS
- 4) DESIGN LOADING: H-10
- 5) CONSTRUCTION JOINTS: SEALED W/BUTYL SEAL
- 6) HEAVY-DUTY TANK TOPS: REINFORCED W/ 5/8" REBAR @ 12" O.C. EACH WAY

**"LOWBOY" OR "LEDGE" SEPTIC TANKS**

**George R. Roberts Co.**  
Precast Concrete Products

RST-1000-LB(-HD), RST-1250(-HD)  
RST-1500-LB(-HD)

[www.georgerobertsco.com](http://www.georgerobertsco.com)

192 Biddeford Road Phone 207-324-6571  
Alfred, Maine 04002 Fax 207-324-8533